

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE: 05 SPS WIM ID: 050200 DATE (mm/dd/yyyy) 10/25/2016
--	--

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 10/25/16
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):
- | | |
|----------------------------|------------|
| a. <u>Inductance Loops</u> | c. <u></u> |
| b. <u>Bending Plates</u> | d. <u></u> |
5. EQUIPMENT MANUFACTURER: IRD iSINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks
- Number of Trucks Compared:
- Number of Test Trucks Used: 2
- Passes Per Truck: 20
- | | Type | Drive Suspension | Trailer Suspension |
|----------|----------|------------------|---------------------|
| Truck 1: | <u>9</u> | <u>air</u> | <u>air</u> |
| Truck 2: | <u>9</u> | <u>air</u> | <u>walking-beam</u> |
| Truck 3: | <u></u> | <u></u> | <u></u> |

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-0.7%</u>	Standard Deviation:	<u>1.3%</u>
Dynamic and Static Single Axle:	<u>-2.1%</u>	Standard Deviation:	<u>2.8%</u>
Dynamic and Static Double Axles:	<u>-0.5%</u>	Standard Deviation:	<u>3.0%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

		Low		High	Runs
a.	<u>Low</u>	<u>58.0</u>	to	<u>62.3</u>	<u>14</u>
b.	<u>Medium</u>	<u>62.4</u>	to	<u>66.8</u>	<u>13</u>
c.	<u>High</u>	<u>66.9</u>	to	<u>71.0</u>	<u>13</u>
d.	<u></u>	<u></u>	to	<u></u>	<u></u>
e.	<u></u>	<u></u>	to	<u></u>	<u></u>

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE: 05 SPS WIM ID: 050200 DATE (mm/dd/yyyy) 10/25/2016
--	--

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 3156 3232

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:	<u>0.0</u>	FHWA Class	<u>-</u>	
FHWA Class 8:	<u>50.0</u>	FHWA Class	<u>-</u>	
		FHWA Class	<u>-</u>	
		FHWA Class	<u>-</u>	

Percent of "Unclassified" Vehicles: 0.0%

Validation Test Truck Run Set - Pre

Person Leading Calibration Effort: Dean Wolf

Contact Information: Phone: 717-975-3550

E-mail: dwolf@ara.com