

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.C1L ✓

DISK ID :

BEGINNING DATE: *01-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *01-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS: Southbound data only due to system problems.

NAME OF PREPARER: <i>Tina L. Ambrosio</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>March 29, 2011</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.E1L ✓

DISK ID :

BEGINNING DATE: *03-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *03-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Tina L. Ambrosio</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>April 20, 2011</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.FIL ✓

DISK ID :

BEGINNING DATE: *04-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *04-30-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>May 24, 2011</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.G1L ✓

DISK ID :

BEGINNING DATE: *05-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *05-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>June 13, 2011</i>	

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.H1L

DISK ID :

BEGINNING DATE: *06-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *06-30-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>July 28, 2011</i>	

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.IIL

DISK ID :

BEGINNING DATE: *07-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *07-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>August 19, 2011</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.J1L ✓

DISK ID :

BEGINNING DATE: *08-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *08-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>September 27, 2011</i>	

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.K1L ✓

DISK ID :

BEGINNING DATE: *09-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *09-30-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>October 25, 2011</i>	

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.L1L ✓

DISK ID :

BEGINNING DATE: *10-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *10-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA ☒ OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT ☒

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>November 16, 2011</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.MIL ✓

DISK ID :

BEGINNING DATE: *11-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *11-30-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: *Mahmood Afrina Khandakar*

PHONE: *(609)-530-3508*

DATE PREPARED: *December 20, 2011*

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40*

FILENAME : C341031.N1L ✓ DISK ID :

BEGINNING DATE: *12-01-2011* BEGINNING TIME: *00:00*

ENDING DATE: *12-31-2011* ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' iSINC Piezo WIM System.*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Mahmood Afrina Khandakar</i>	PHONE: <i>(609)-530-3508</i>
DATE PREPARED: <i>January 13, 2012</i>	

SHEET 13 LTTP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): *NJ-55*

MILEPOST NO. OR LOCATION (THIS SESSION): *MP 36.5, Vineland Township, 2.8 miles South of Route US-40.*

FILENAME : W341031. C1L ✓ DISK ID:
V341031. C1L

BEGINNING DATE: *01-01-2011*

BEGINNING TIME: *00:00*

ENDING DATE: *01-31-2011*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM *X* OTHER

EQUIPMENT MAKE/MODEL# *International Road Dynamics iSINC Piezo WIM System*

SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: *Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.*

COMMENTS: No data for northbound due to system problems.

NAME OF PREPARER: *Tina L. Ambrosio*
DATE PREPARED: *March 29, 2011*

PHONE: *(609)-530-3508*

SHEET 13 LTTP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031. EIL ✓ DISK-ID:
V341031. EIL

BEGINNING DATE: **03-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **03-31-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: Tina L. Ambrosio	PHONE: (609)-530-3508
DATE PREPARED: April 20, 2011	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031. FIL ☒ DISK ID:
V341031. FIL

BEGINNING DATE: **04-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **04-30-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: Mahmood Afrina Khandakar	PHONE: (609)-530-3508
DATE PREPARED: May 24, 2011	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031.FIL ✓
V341031.FIL

DISK ID:

BEGINNING DATE: **04-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **04-30-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Mahmood Afrina Khandakar**
DATE PREPARED: **June 13, 2011**

PHONE: **(609)-530-3508**

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031. H1L DISK ID:
V341031. H1L

BEGINNING DATE: **06-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **06-30-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: Mahmood Afrina Khandakar	PHONE: (609)-530-3508
DATE PREPARED: July 28, 2011	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031.11L DISK ID:
V341031.11L

BEGINNING DATE: **07-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **07-31-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Mahmood Afrina Khandakar**
DATE PREPARED: **August 19, 2011**

PHONE: **(609)-530-3508**

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031.J1L ✓ DISK ID:
V341031.J1L

BEGINNING DATE: **08-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **08-31-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Mahmood Afrina Khandakar**
DATE PREPARED: **September 27, 2011**

PHONE: **(609)-530-3508**

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031. K1L ✓ DISK ID:
V341031. K1L

BEGINNING DATE: **09-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **09-30-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Mahmood Afrina Khandakar**
DATE PREPARED: **October 25, 2011**

PHONE: **(609)-530-3508**

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID [NJ-55]
	*STATE CODE [3 4]
	*SHRP SECTION ID [1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 36.5, Vineland Township, 2.8 miles South of Route US-40.**

FILENAME : W341031.L1L ✓ DISK ID:
V341031.L1L

BEGINNING DATE: **10-01-2011**

BEGINNING TIME: **00:00**

ENDING DATE: **10-31-2011**

ENDING TIME: **24:00**

COUNT DURATION: **1** [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics iSINC Piezo WIM System**

SENSOR TYPE: **Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Mahmood Afrina Khandakar**
DATE PREPARED: **November 16, 2011**

PHONE: **(609)-530-3508**

LTPP TRAFFIC DATA

VEHICLE WEIGHT DATA
TRANSMITTAL FORM

*STATE CODE

[3 4]

*SHRP SECTION ID

[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): *NJ-55*MILEPOST NO. OR LOCATION (THIS SESSION): *MP 36.5, Vineland Township, 2.8 miles
South of Route US-40.*FILENAME : W341031.MIL ✓
V341031.MIL

DISK ID:

BEGINNING DATE: *11-01-2011*BEGINNING TIME: *00:00*ENDING DATE: *11-30-2011*ENDING TIME: *24:00*COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHSWEIGHT SCALE TYPE: PORT. WIM PERM. WIM *X* OTHEREQUIPMENT MAKE/MODEL# *International Road Dynamics iSINC Piezo WIM System*SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card 6 digit Truck Weight study

7-card FHWA 13 bin in cols. 22-23

W-card *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: *Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.*

COMMENTS:

NAME OF PREPARER: *Mahmood Afrina Khandakar*PHONE: *(609)-530-3508*DATE PREPARED: *December 20, 2011*

VEHICLE WEIGHT DATA
TRANSMITTAL FORM

*STATE CODE

[3 4]

*SHRP SECTION ID

[1 0 3 1]

HIGHWAY RT. NO. (THIS SESSION): *NJ-55*MILEPOST NO. OR LOCATION (THIS SESSION): *MP 36.5, Vineland Township, 2.8 miles
South of Route US-40.*FILENAME : W341031.N1L
V341031.N1L

DISK ID:

BEGINNING DATE: *12-01-2011*BEGINNING TIME: *00:00*ENDING DATE: *12-31-2011*ENDING TIME: *24:00*COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHSWEIGHT SCALE TYPE: PORT. WIM PERM. WIM *X* OTHEREQUIPMENT MAKE/MODEL# *International Road Dynamics iSINC Piezo WIM System*SENSOR TYPE: *Each lane has two (2) loops and two (2) Class I piezoelectric WIM sensors, (L-P-P-L) configuration.*

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card 6 digit Truck Weight study

7-card FHWA 13 bin in cols. 22-23

W-card *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6
DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH
SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION
SCHEME TO THE FHWA 13 CLASS SYSTEM.METHOD OF CALIBRATION AND FREQUENCY: *Calibration is field validated on each site once a
year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum
of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent
of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the
calibration vehicles and the weights recorded are averaged using only the consistently measured GVW.
Another 10 or more passes are then made after inputting the new changes to confirm the calibration
tolerances. The process is repeated until the required tolerance is satisfied.*

COMMENTS:

NAME OF PREPARER: *Mahmood Afrina Khandakar*PHONE: *(609)-530-3508*DATE PREPARED: *January 13, 2012*

Entered 6/14/11 *re*

SHEET 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	*STATE ASSIGNED ID [NJ-55] *STATE CODE [34] *SHRP SECTION ID [1031]
--	---

SITE CALIBRATION INFORMATION

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR) [04/02/2011]

2. * TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH

3. * REASON FOR CALIBRATION

☐ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH
☐ EQUIPMENT REPLACEMENT ☐ TRAINING
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION
☒ OTHER (SPECIFY) SEMI-ANNUAL CALIBRATION

4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):

☐ BARE ROUND PIEZO CERAMIC ☒ BARE FLAT PIEZO ☐ BENDING PLATES
☐ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO
☐ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS
☐ OTHER (SPECIFY) _____

5. EQUIPMENT MANUFACTURER IRD
WIM SYSTEM CALIBRATION SPECIFICS**

6.**CALIBRATION TECHNIQUE USED:

☐ TRAFFIC STREAM -- ☒ Y STATIC SCALE (Y/N) ☒ TEST TRUCKS

1 NUMBER OF TRUCKS COMPARED

1 NUMBER OF TEST TRUCKS USED

10 PASSES PER TRUCK

TYPE PER FHWA 13 BIN SYSTEM

SUSPENSION: 1 - AIR; 2 - LEAF SPRING

3 - OTHER (DESCRIBE)

TRUCK TYPE SUSPENSION

1 class 9 2

2 _____

3 _____

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)

MEAN DIFFERENCE BETWEEN ---

STATIC GVW (S)64.6

STANDARD DEVIATION BY LANE:

LANE 1 sensor 1: .27 sensor 2: 2.29

LANE 2 sensor 1: 2.39 sensor 2: 2.18

LANE 3 sensor 1: 1.38 sensor 2: 1.87

LANE 4 sensor 1: 1.75 sensor 2: 3.97

*60W
Avg Mean Diff 0.99
Avg SD 60W 1.75*

*Please see accomp. data file:

CDS_551_1031.xls

8. 1 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED

9. DEFINE THE SPEED RANGES USED (MPH) 55-62

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED):

NB_SLOW (LANE 1) sensor 1: 9250 sensor 2: 8000

NB_PASS (LANE 2) sensor 1: 16000 sensor 2: 14000

SB_SLOW (LANE 1) sensor 1: 10000 sensor 2: 9000

SB_PASS (LANE 2) sensor 1: 9750 sensor 2: 8740

Avg. 8005

11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) Y

IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: The auto-calibration is defined in 24 hours intervals. The method is set to *adjust after 50 trucks*, the number of auto-calibration class 9 trucks for the interval and the sum of front axle weights for the period are calculated and added to a running totals read from the ASCII file. If the number of trucks is less than 50 *trucks required before adjust*, then the new count and sum are stored in the file. If the number of accumulated trucks is greater than the user entered, then, as above, the error between the calculated mean front axle weight and the user entered Population Mean is determined. Temperature sensor is another factor that has an influence on auto-calibration process.

CLASSIFIER TEST SPECIFICS***

12. *** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

☐ VIDEO ☐ MANUAL ☐ PARALLEL CLASSIFIERS

13. METHOD TO DETERMINE LENGTH OF COUNT ☐ TIME ☐ NUMBER OF TRUCKS

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

*** FHWA CLASS 9 _____ FHWA CLASS _____

*** FHWA CLASS 8 _____ FHWA CLASS _____

_____ FHWA CLASS _____

_____ FHWA CLASS _____

*** PERCENT AUNCLASSIFIED= VEHICLES: _____

PERSON LEADING CALIBRATION EFFORT: BRIAN BRITTON
 CONTACT INFORMATION: M. AFRINA KHANDAKAR (609)530-3508

