

SHEET 12 LTTP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME :

DISK ID :

BEGINNING DATE: *01-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *01-31-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A*

NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE

PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: *Zoltan Zeisky*
DATE PREPARED: *March 1, 2004*

PHONE: *(609)-530-2992*

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT) : *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME :

DISK ID :

BEGINNING DATE: *02-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *02-29-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A*

NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT:

PORTABLE

PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609)-530-2992</i>
DATE PREPARED: <i>March 8, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT) : *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME :

DISK ID :

BEGINNING DATE: *03-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *03-31-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* ☐ HOURS ☐ DAYS ☒ MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A*

NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE

PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609)-530-2992</i>
DATE PREPARED: <i>April 22, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT) : *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME :

DISK ID :

BEGINNING DATE: *04-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *04-30-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* ☐ HOURS ☐ DAYS ☒ MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X*

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A*

NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE

PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609)-530-2992</i>
DATE PREPARED: <i>May 25, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT) : *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME :

DISK ID :

BEGINNING DATE: *05-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *05-31-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609)-530-2992</i>
DATE PREPARED: <i>June 17, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME: C341638.HLE

DISK ID:

BEGINNING DATE: *06-22-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *06-30-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>July 21, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME: C341638.I1E

DISK ID:

BEGINNING DATE: *07-22-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *07-31-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>August 26, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID [NJ-55]
	*STATE CODE [3 4]
	*SHRP SECTION ID [1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME: C341638.J1E

DISK ID:

BEGINNING DATE: *08-22-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *08-31-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>September 20, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS COUNT): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME: C341638.L1E

DISK ID:

BEGINNING DATE: ***10-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***10-31-2004***

ENDING TIME: ***24:00***

COUNT DURATION: ***1*** [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA ***X*** OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: ***N/A*** NO. OF BINS: ***N/A***

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT ***X***

EQUIPMENT MAKE/MODEL#: ***International Road Dynamics' Piezo WIM System.***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>December 8, 2004</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): *NJ-55 NB*

MILEPOST NO. OR LOCATION (THIS COUNT): *MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.*

FILENAME: C341638.M1E

DISK ID:

BEGINNING DATE: *11-01-2004*

BEGINNING TIME: *00:00*

ENDING DATE: *11-30-2004*

ENDING TIME: *24:00*

COUNT DURATION: *1* [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA *X* OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: *N/A* NO. OF BINS: *N/A*

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT *X*

EQUIPMENT MAKE/MODEL#: *International Road Dynamics' Piezo WIM System.*

SENSOR TYPE: *Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.*
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>January 13, 2005</i>	

SHEET 12 LTPP TRAFFIC DATA CLASSIFICATION DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS COUNT): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS COUNT): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME: C341638.N1E

DISK ID:

BEGINNING DATE: ***12-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***12-31-2004***

ENDING TIME: ***24:00***

COUNT DURATION: ***1*** [] HOURS [] DAYS [X] MONTHS

VEHICLE CLASSIFICATION METHOD: FHWA ***X*** OTHER

NAME OF AGENCY CLASSIFICATION SCHEME: ***N/A*** NO. OF BINS: ***N/A***

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 BIN SYSTEM.

TYPE OF AVC EQUIPMENT: PORTABLE PERMANENT ***X***

EQUIPMENT MAKE/MODEL#: ***International Road Dynamics' Piezo WIM System.***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***
Sensor status:

ADJUSTMENT FACTORS FOR ESTIMATING AVERAGE ANNUAL VOLUMES BY CLASSIFICATION:

GENERAL FACTORS:

CLASS SPECIFIC FACTORS (PROVIDE BY CLASS OF CLASS GROUPS):

COMMENTS:

NAME OF PREPARER: <i>Brian C. Britton</i>	PHONE: <i>(609)-530-3478</i>
DATE PREPARED: <i>January 25, 2005</i>	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : V341638.C1E
C341638.C1E
W341638.C1E

DISK ID:

BEGINNING DATE: **01-01-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **01-31-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS: Missing data on January 2 and 29, 2004 due to system problems.

NAME OF PREPARER: Zoltan Zeisky	PHONE: (609) 530-2992
DATE PREPARED: March 1, 2004	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS SESSION): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME : V341638.D1E
C341638.D1E
W341638.D1E

DISK ID:

BEGINNING DATE: ***02-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***02-29-2004***

ENDING TIME: ***24:00***

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM ***X*** OTHER

EQUIPMENT MAKE/MODEL# ***International Road Dynamics Piezo WIM System***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card ***X***

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: ***Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.***

COMMENTS: Missing data on February 2 and 29, due to system problems.

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609) 530-2992</i>
DATE PREPARED: <i>March 8, 2004</i>	

SHEET 13 LTTP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS SESSION): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME : V341638.E3E
C341638.E3E
W341638.E3E

DISK ID:

BEGINNING DATE: ***03-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***03-31-2004***

ENDING TIME: ***24:00***

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM ***X*** OTHER

EQUIPMENT MAKE/MODEL# ***International Road Dynamics Piezo WIM System***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card ***X***

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: ***Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.***

COMMENTS: Missing data on March 1, 2 and 29, due to system problems.

NAME OF PREPARER: <i>Zoltan Zeisky</i>	PHONE: <i>(609) 530-2992</i>
DATE PREPARED: <i>April 22, 2004</i>	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : V341638.F1E
C341638.F1E
W341638.F1E

DISK ID:

BEGINNING DATE: **04-01-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **04-30-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS: Missing data on April 15, 20 thru 22 and 30, due to system problems.

NAME OF PREPARER: Zoltan Zeisky	PHONE: (609) 530-2992
DATE PREPARED: May 25, 2004	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS SESSION): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME : V341638.G1E
C341638.G1E
W341638.G1E

DISK ID:

BEGINNING DATE: ***05-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***05-31-2004***

ENDING TIME: ***24:00***

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM ***X*** OTHER

EQUIPMENT MAKE/MODEL# ***International Road Dynamics Piezo WIM System***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card ***X***

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: ***Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.***

COMMENTS: Site calibrated on May 1, 2004.

NAME OF PREPARER: ***Zoltan Zeisky***
DATE PREPARED: ***June 17, 2004***

PHONE: ***(609) 530-2992***

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : W341638.HLE
V341638.HLE

DISK ID:

BEGINNING DATE: **06-22-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **06-30-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS: NO DATA ON JUNE 1 - 21 DUE TO SYSTEM PROBLEMS.

NAME OF PREPARER: Brian C. Britton	PHONE: (609) 530-3478
DATE PREPARED: July 21, 2004	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : W341638.I1E
V341638.I1E

DISK ID:

BEGINNING DATE: **07-01-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **07-31-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: **Brian C. Britton**
DATE PREPARED: **August 26, 2004**

PHONE: **(609) 530-3478**

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : W341638.J1E
V341638.J1E

DISK ID:

BEGINNING DATE: **08-01-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **08-31-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: Brian C. Britton	PHONE: (609) 530-3478
DATE PREPARED: September 20, 2004	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): **NJ-55 NB**

MILEPOST NO. OR LOCATION (THIS SESSION): **MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.**

FILENAME : W341638.L1E
V341638.L1E

DISK ID:

BEGINNING DATE: **10-01-2004**

BEGINNING TIME: **00:00**

ENDING DATE: **10-31-2004**

ENDING TIME: **24:00**

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM **X** OTHER

EQUIPMENT MAKE/MODEL# **International Road Dynamics Piezo WIM System**

SENSOR TYPE: **Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.**

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card **X**

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: **Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.**

COMMENTS:

NAME OF PREPARER: Brian C. Britton	PHONE: (609) 530-3478
DATE PREPARED: December 8, 2004	

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS SESSION): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME : W341638.M1E
V341638.M1E

DISK ID:

BEGINNING DATE: ***11-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***11-30-2004***

ENDING TIME: ***24:00***

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM ***X*** OTHER

EQUIPMENT MAKE/MODEL# ***International Road Dynamics Piezo WIM System***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card ***X***

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: ***Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.***

COMMENTS:

NAME OF PREPARER: ***Brian C. Britton***
DATE PREPARED: ***January 13, 2005***

PHONE: ***(609) 530-3478***

SHEET 13 LTPP TRAFFIC DATA VEHICLE WEIGHT DATA TRANSMITTAL FORM	*STATE ASSIGNED ID	[NJ-55]
	*STATE CODE	[3 4]
	*SHRP SECTION ID	[1 6 3 8]

HIGHWAY RT. NO. (THIS SESSION): ***NJ-55 NB***

MILEPOST NO. OR LOCATION (THIS SESSION): ***MP 58.7, Deptford Township, 1.6 mile North of Route NJ-47.***

FILENAME : W341638.N1E
V341638.N1E

DISK ID:

BEGINNING DATE: ***12-01-2004***

BEGINNING TIME: ***00:00***

ENDING DATE: ***12-31-2004***

ENDING TIME: ***24:00***

COUNT DURATION: 1 [] HOURS [] DAYS [X] MONTHS

WEIGHT SCALE TYPE: PORT. WIM PERM. WIM ***X*** OTHER

EQUIPMENT MAKE/MODEL# ***International Road Dynamics Piezo WIM System***

SENSOR TYPE: ***Each lane has a single upstream loop and two (2) class I piezoelectric WIM sensors.***

VEHICLE CLASSIFICATION METHOD:

7-card FHWA 13 bin in cols. 18-19

7-card FHWA 13 bin in cols. 22-23

7-card 6 digit Truck Weight study

W-card ***X***

OTHER

NAME OF AGENCY CLASSIFICATION SCHEME:

NO. OF BINS

NOTE: IF NOT PREVIOUSLY PROVIDED TO SHRP/LTPP, PLEASE ATTACH SHEET 6 DESCRIBING THE VEHICLE CLASSIFICATION CATEGORIES AND ALSO ATTACH SHEET 7 DESCRIBING HOW THE AGENCY WOULD CONVERT ITS CLASSIFICATION SCHEME TO THE FHWA 13 CLASS SYSTEM.

METHOD OF CALIBRATION AND FREQUENCY: ***Calibration is field validated on each site once a year using one 3S2 vehicle loaded and statically weighed at about 70,000 to 80,000 pounds. A minimum of 20 passes is made per lane at highway speeds or until a consistent calibration tolerance of ± 5 percent of the gross test vehicle weight is achieved. The initial run consists of about 10 or more passes of the calibration vehicles and the weights recorded are averaged using only the consistently measured GVW. Another 10 or more passes are then made after inputting the new changes to confirm the calibration tolerances. The process is repeated until the required tolerance is satisfied.***

COMMENTS:

NAME OF PREPARER: ***Brian C. Britton***
DATE PREPARED: ***January 25, 2005***

PHONE: ***(609) 530-3478***

SHEET 16

LTPP MONITORED TRAFFIC DATA

SITE CALIBRATION SUMMARY

*STATE ASSIGNED ID

[NJ-55]

*STATE CODE

[34]

*SHRP SECTION ID

[1638]

SITE CALIBRATION INFORMATION

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR)

[05 / 01 / 2004]

2. * TYPE OF EQUIPMENT CALIBRATED

X

 WIM

CLASSIFIER

BOTH

3. * REASON FOR CALIBRATION

REGULARLY SCHEDULED SITE VISIT

EQUIPMENT REPLACEMENT

DATA TRIGGERED SYSTEM REVISION

X OTHER (SPECIFY) ANNUAL CALIBRATION

RESEARCH

TRAINING

NEW EQUIPMENT INSTALLATION

4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):

BARE ROUND PIEZO CERAMIC

BARE FLAT PIEZO

BENDING PLATES

X CHANNELIZED ROUND PIEZO

LOAD CELLS

QUARTZ PIEZO

CHANNELIZED FLAT PIEZO

X INDUCTANCE LOOPS

CAPACITANCE PADS

OTHER (SPECIFY)

5. EQUIPMENT MANUFACTURER

IRD

WIM SYSTEM CALIBRATION SPECIFICS**

6.**CALIBRATION TECHNIQUE USED:

TRAFFIC STREAM -- Y STATIC SCALE (Y/N)

X TEST TRUCKS

NUMBER OF TRUCKS COMPARED

1 NUMBER OF TEST TRUCKS USED

PASSES PER TRUCK

TRUCK	TYPE	SUSPENSION
1	Class 9	2
2		
3		

TYPE PER FHWA 13 BIN SYSTEM

SUSPENSION: 1 - AIR; 2 - LEAF SPRING

3 - OTHER (DESCRIBE)

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)

MEAN DIFFERENCE BETWEEN ---

STATIC GVW: (S)58.76

STANDARD DEVIATION BY LANE:

Lane 1 Sensor 1: Down

Lane 1 Sensor 2: Down

Lane 2 Sensor 1: 0.76

Lane 2 Sensor 2: 1.03

*Please see accomp. data file:

CDS_552N_1638.xls

8. 1 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED

9. DEFINE THE SPEED RANGES USED (MPH)

65-66

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) :

NB_SLOW (Lane 1) Sensor 1: Down Sensor 2: Down

NB_PASS (Lane 2) Sensor 1: 0.5597 Sensor 2: 0.4916

11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) Y

IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: The auto-calibration is defined in 24 hours intervals. The method is set to *adjust after 50 trucks*, the number of auto-calibration class 9 trucks for the interval and the sum of front axle weights for the period are calculated and added to a running totals read from the ASCII file. If the number of trucks is less than 50 *trucks required before adjust*, then the new count and sum are stored in the file. If the number of accumulated trucks is greater than the user entered, then, as above, the error between the calculated mean front axle weight and the user entered Population Mean is determined. Temperature sensor is another factor that has an influence on auto-calibration process.

CLASSIFIER TEST SPECIFICS***

12.*** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

VIDEO MANUAL PARALLEL CLASSIFIERS

13. METHOD TO DETERMINE LENGTH OF COUNT

TIME

NUMBER OF TRUCKS

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

*** FHWA CLASS 9

*** FHWA CLASS 8

FHWA CLASS

FHWA CLASS

FHWA CLASS

FHWA CLASS

*** PERCENT AUNCLASSIFIED≅ VEHICLES:

PERSON LEADING CALIBRATION EFFORT: BRION BRITTON and ROBERT JANKOWICZ

CONTACT INFORMATION: ZOLTAN G. ZEISKY (609) 530-2992