

<b>Traffic Sheet 16</b> <b>LTPP MONITORED TRAFFIC DATA</b> <b>SITE CALIBRATION SUMMARY</b>	STATE CODE: 41 SPS WIM ID: 41AA00 DATE (mm/dd/yyyy) 6/26/2018
--	---

### SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 6/26/18
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):
- a. Inductance Loops c.
- b. Quartz Piezo d.
5. EQUIPMENT MANUFACTURER: IRD iSINC

### WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks
- Number of Trucks Compared: 2
- Number of Test Trucks Used: 2
- Passes Per Truck: 20
- |          | Type     | Drive Suspension | Trailer Suspension |
|----------|----------|------------------|--------------------|
| Truck 1: | <u>9</u> | <u>air</u>       | <u>air</u>         |
| Truck 2: | <u>9</u> | <u>air</u>       | <u>air</u>         |
| Truck 3: | <u></u>  | <u></u>          | <u></u>            |

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-0.8%</u>	Standard Deviation:	<u>2.2%</u>
Dynamic and Static Single Axle:	<u>-0.1%</u>	Standard Deviation:	<u>2.9%</u>
Dynamic and Static Double Axles:	<u>-1.0%</u>	Standard Deviation:	<u>0.5%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

		Low		High	Runs
a.	<u>Low</u>	<u>49.0</u>	to	<u>52.7</u>	<u>14</u>
b.	<u>Medium</u>	<u>52.8</u>	to	<u>56.4</u>	<u>14</u>
c.	<u>High</u>	<u>56.5</u>	to	<u>60.0</u>	<u>12</u>
d.	<u></u>	<u></u>	to	<u></u>	<u></u>
e.	<u></u>	<u></u>	to	<u></u>	<u></u>

<b>Traffic Sheet 16</b> <b>LTPP MONITORED TRAFFIC DATA</b> <b>SITE CALIBRATION SUMMARY</b>	STATE CODE: 41 SPS WIM ID: 41AA00 DATE (mm/dd/yyyy) 6/26/2018
--	---

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 2900 2900

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

**CLASSIFIER TEST SPECIFICS**

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:	<u>0.0</u>	FHWA Class	<u>5</u>	-	<u>-25.0</u>
FHWA Class 8:	<u>167.0</u>	FHWA Class	<u>          </u>	-	<u>          </u>
		FHWA Class	<u>          </u>	-	<u>          </u>
		FHWA Class	<u>          </u>	-	<u>          </u>

Percent of "Unclassified" Vehicles: 0.0%

ENTERED BY CO  
2020/02/27

Test Truck Run Set - Pre

Person Leading Calibration Effort: Dean Wolf

Contact Information: Phone: 717-975-3550

E-mail: [dwolf@ara.com](mailto:dwolf@ara.com)