

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	47
	SPS WIM ID:	470600
	DATE (mm/dd/yyyy)	2/15/2011

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 2/15/11
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):
- | | |
|----------------------------|------------|
| a. <u>Inductance Loops</u> | c. <u></u> |
| b. <u>Quartz Piezo</u> | d. <u></u> |
5. EQUIPMENT MANUFACTURER: IRD ISINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks
- Number of Trucks Compared:
- Number of Test Trucks Used: 2
- Passes Per Truck: 21

	Type	Drive Suspension	Trailer Suspension
Truck 1:	<u>9</u>	<u>air</u>	<u>air</u>
Truck 2:	<u>10</u>	<u>air</u>	<u>air</u>
Truck 3:	<u>0</u>	<u>0</u>	<u>0</u>

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-4.6%</u>	Standard Deviation:	<u>1.9%</u>
Dynamic and Static Single Axle:	<u>-4.4%</u>	Standard Deviation:	<u>2.8%</u>
Dynamic and Static Double Axles:	<u>-4.3%</u>	Standard Deviation:	<u>2.4%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

	Low		High	Runs
a. <u>Low</u>	-	<u>58.0</u>	to <u>62.0</u>	<u>13</u>
b. <u>Medium</u>	-	<u>62.1</u>	to <u>66.1</u>	<u>16</u>
c. <u>High</u>	-	<u>66.2</u>	to <u>70.0</u>	<u>12</u>
d. <u></u>	-	<u></u>	to <u></u>	<u></u>
e. <u></u>	-	<u></u>	to <u></u>	<u></u>

ENTERED NOV 28 11 A

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	47
	SPS WIM ID:	470600
	DATE (mm/dd/yyyy)	2/15/2011

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 3104 3295

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

13. METHOD TO DETERMINE LENGTH OF COUNT: _____

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:	0.0	FHWA Class	-	
FHWA Class 8:	50.0	FHWA Class	-	
		FHWA Class	-	
		FHWA Class	-	

Percent of "Unclassified" Vehicles: 0.0%

Validation Test Truck Run Set - Pre

Person Leading Calibration Effort:	Kevin Trousdale		
Contact Information:	Phone:	717-975-3550	
	E-mail:	ktrousdale@ara.com	

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	47
	SPS WIM ID:	470600
	DATE (mm/dd/yyyy)	2/16/2011

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 2/16/11
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):
- | | |
|----------------------------|------------|
| a. <u>Inductance Loops</u> | c. <u></u> |
| b. <u>Quartz Piezo</u> | d. <u></u> |
5. EQUIPMENT MANUFACTURER: IRD iSINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks
- Number of Trucks Compared:
- Number of Test Trucks Used: 2
- Passes Per Truck: 20
- | | Type | Drive Suspension | Trailer Suspension |
|----------|-----------|------------------|--------------------|
| Truck 1: | <u>9</u> | <u>air</u> | <u>air</u> |
| Truck 2: | <u>10</u> | <u>air</u> | <u>air</u> |
| Truck 3: | <u></u> | <u></u> | <u></u> |

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-1.3%</u>	Standard Deviation:	<u>1.9%</u>
Dynamic and Static Single Axle:	<u>-2.9%</u>	Standard Deviation:	<u>4.4%</u>
Dynamic and Static Double Axles:	<u>-1.1%</u>	Standard Deviation:	<u>2.1%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

		Low		High	Runs
a.	<u>Low</u>	<u>58.0</u>	to	<u>62.0</u>	<u>14</u>
b.	<u>Medium</u>	<u>62.1</u>	to	<u>66.1</u>	<u>12</u>
c.	<u>High</u>	<u>66.2</u>	to	<u>70.0</u>	<u>14</u>
d.	<u></u>	<u></u>	to	<u></u>	<u></u>
e.	<u></u>	<u></u>	to	<u></u>	<u></u>

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE: 47 SPS WIM ID: 470600 DATE (mm/dd/yyyy) 2/16/2011
--	---

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 3044 | 3231

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE
CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:	0.0	FHWA Class	-	
FHWA Class 8:	33.0	FHWA Class	-	
		FHWA Class	-	
		FHWA Class	-	

Percent of "Unclassified" Vehicles: 0.0%

Validation Test Truck Run Set - Post

Person Leading Calibration Effort:	Kevin Trousdale		
Contact Information:	Phone:	717-975-3550	
	E-mail:	ktrousdale@ara.com	