

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE: 48 SPS WIM ID: 48AA00 DATE (mm/dd/yyyy) 2/13/2018
--	---

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 2/13/18
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):
- | | |
|----------------------------|------------|
| a. <u>Inductance Loops</u> | c. <u></u> |
| b. <u>Quartz Piezo</u> | d. <u></u> |
5. EQUIPMENT MANUFACTURER: IRD iSINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks
- | | |
|-----------------------------|-----------|
| Number of Trucks Compared: | <u>2</u> |
| Number of Test Trucks Used: | <u>2</u> |
| Passes Per Truck: | <u>20</u> |
- | | | | |
|----------|----------|------------------|--------------------|
| | Type | Drive Suspension | Trailer Suspension |
| Truck 1: | <u>9</u> | <u>air</u> | <u>air</u> |
| Truck 2: | <u>9</u> | <u>air</u> | <u>torsion</u> |
| Truck 3: | <u></u> | <u></u> | <u></u> |

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-0.1%</u>	Standard Deviation:	<u>2.3%</u>
Dynamic and Static Single Axle:	<u>4.9%</u>	Standard Deviation:	<u>3.2%</u>
Dynamic and Static Double Axles:	<u>-0.8%</u>	Standard Deviation:	<u>4.1%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

		Low		High	Runs
a.	<u>Low</u>	<u>64.0</u>	to	<u>67.7</u>	<u>12</u>
b.	<u>Medium</u>	<u>67.8</u>	to	<u>71.4</u>	<u>12</u>
c.	<u>High</u>	<u>71.5</u>	to	<u>75.0</u>	<u>16</u>
d.	<u></u>	<u></u>	to	<u></u>	<u></u>
e.	<u></u>	<u></u>	to	<u></u>	<u></u>

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE: 48 SPS WIM ID: 48AA00 DATE (mm/dd/yyyy) 2/13/2018
--	---

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 2759 2759

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:	<u>0.0</u>	FHWA Class <u>5</u>	-	<u>0.0</u>
FHWA Class 8:	<u>0.0</u>	FHWA Class <u> </u>	-	<u> </u>
		FHWA Class <u> </u>	-	<u> </u>
		FHWA Class <u> </u>	-	<u> </u>

Percent of "Unclassified" Vehicles: 0.0%

ENTERED BY CO
2020/02/27

Validation Test Truck Run Set - Pre

Person Leading Calibration Effort: Dean J. Wolf, ARA

Contact Information: Phone: 717-975-3550

E-mail: dwolf@ara.com