

SHEET 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	*STATE ASSIGNED ID	[P01]
	*STATE CODE	[53]
	*SHRP SECTION ID	[6020]

SITE CALIBRATION INFORMATION

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR) [03/25/2003]
2. * TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH
3. * REASON FOR CALIBRATION
☒ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH
☐ EQUIPMENT REPLACEMENT ☐ TRAINING
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION
☐ OTHER (SPECIFY) _____
4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):
☐ BARE ROUND PIEZO CERAMIC ☐ BARE FLAT PIEZO ☐ BENDING PLATES
☐ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO
☒ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS
☐ OTHER (SPECIFY) _____
5. EQUIPMENT MANUFACTURER INTERNATIONAL ROAD DYNAMICS (IRD)

WIM SYSTEM CALIBRATION SPECIFICS**

- 6.** CALIBRATION TECHNIQUE USED:
☒ TRAFFIC STREAM -- ☐ STATIC SCALE (Y/N) ☐ TEST TRUCKS
☐ NUMBER OF TRUCKS COMPARED ☐ NUMBER OF TEST TRUCKS USED

	PASSES PER TRUCK		
	TRUCK	TYPE	SUSPENSION
TYPE PER FHWA 13 BIN SYSTEM	1	_____	_____
SUSPENSION: 1 - AIR; 2 - LEAF SPRING	2	_____	_____
3 - OTHER (DESCRIBE)	3	_____	_____
7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)
 MEAN DIFFERENCE BETWEEN ---
 DYNAMIC AND STATIC GVW _____ STANDARD DEVIATION _____
 DYNAMIC AND STATIC SINGLE AXLES _____ STANDARD DEVIATION _____
 DYNAMIC AND STATIC DOUBLE AXLES _____ STANDARD DEVIATION _____
8. _____ NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED
9. DEFINE THE SPEED RANGES USED (MPH) _____
10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 0.47001
- 11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) Y
 IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: _____

CLASSIFIER TEST SPECIFICS***

- 12.*** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:
☐ VIDEO ☐ MANUAL ☒ PARALLEL CLASSIFIERS