

<div>SHEET 16</div> <div>LTPP MONITORED TRAFFIC DATA</div> <div>SITE CALIBRATION SUMMARY</div>	<div>*STATE ASSIGNED ID [P14]</div> <div>*STATE CODE [53]</div> <div>*SHRP SECTION ID [7322 NB]</div>
--	---

SITE CALIBRATION INFORMATION

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR) [06 /06 /2006]

2. * TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH

3. * REASON FOR CALIBRATION
☒ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH
☐ EQUIPMENT REPLACEMENT ☐ TRAINING
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION
☐ OTHER (SPECIFY) _____

4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):
☐ BARE ROUND PIEZO CERAMIC ☒ BARE FLAT PIEZO ☐ BENDING PLATES
☐ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO
☐ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS
☐ OTHER (SPECIFY) _____

5. EQUIPMENT MANUFACTURER: INTERNATIONAL ROAD DYNAMIC

WIM SYSTEM CALIBRATION SPECIFICS**

6. ** CALIBRATION TECHNIQUE USED:
☐ TRAFFIC STREAM -- ☐ STATIC SCALE (Y/N) ☒ TEST TRUCKS
☒ NUMBER OF TRUCKS COMPARED ☐ 1 NUMBER OF TEST TRUCKS USED

	PASSES PER TRUCK		
	TRUCK	TYPE	SUSPENSION
TYPE PER FHWA 13 BIN SYSTEM	1	Class 9	<input type="checkbox"/> Air
SUSPENSION: 1 - AIR; 2 - LEAF SPRING	2		
3 - OTHER (DESCRIBE)	3		

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)
MEAN DIFFERENCE BETWEEN ---
DYNAMIC AND STATIC GVW -3.20% STANDARD DEVIATION 1.95%
DYNAMIC AND STATIC SINGLE AXLES 2.55% STANDARD DEVIATION 4.16%
DYNAMIC AND STATIC DOUBLE AXLES -3.66% STANDARD DEVIATION 3.10%

8. ☐ 1 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED

9. DEFINE THE SPEED RANGES USED (MPH) ☐ 55 mph _____

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) Sensor #1= .321, Sensor #2= .260

11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) ☒ Yes
IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: Site is set to auto-calibrate every 48 hours. 3 ranges are used. Range #1 is set at 8,000 pounds front axle for trucks weigh up to 32,000 pounds. Range #2 is set for 10,000 pounds front axle for trucks weigh between 32,001 to 50,000 pounds. Range #3 is set for 11,000 pounds front axle for trucks weigh greater than 50,000 pounds.

CLASSIFIER TEST SPECIFICS***

12.*** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:
☐ VIDEO ☐ MANUAL ☐ PARALLEL CLASSIFIERS

13. METHOD TO DETERMINE LENGTH OF COUNT ☐ TIME ☐ NUMBER OF TRUCKS

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:
*** FHWA CLASS 9 _____ FHWA CLASS _____
*** FHWA CLASS 8 _____ FHWA CLASS _____
FHWA CLASS _____
FHWA CLASS _____
*** PERCENT "UNCLASSIFIED" VEHICLES: _____

ENTD JUL 26 2006

<div>SHEET 16</div> <div>LTPP MONITORED TRAFFIC DATA</div> <div>SITE CALIBRATION SUMMARY</div>	<div>*STATE ASSIGNED ID [P14]</div> <div>*STATE CODE [53]</div> <div>*SHRP SECTION ID [7322 SB]</div>
--	---

SITE CALIBRATION INFORMATION

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR) [06 /06 /2006]

2. * TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH

3. * REASON FOR CALIBRATION
☒ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH
☐ EQUIPMENT REPLACEMENT ☐ TRAINING
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION
☐ OTHER (SPECIFY) _____

4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):
☐ BARE ROUND PIEZO CERAMIC ☒ BARE FLAT PIEZO ☐ BENDING PLATES
☐ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO
☐ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS
☐ OTHER (SPECIFY) _____

5. EQUIPMENT MANUFACTURER: INTERNATIONAL ROAD DYNAMIC

WIM SYSTEM CALIBRATION SPECIFICS**

6. ** CALIBRATION TECHNIQUE USED:
☐ TRAFFIC STREAM -- ☐ STATIC SCALE (Y/N) ☒ TEST TRUCKS

☐ 1 NUMBER OF TRUCKS COMPARED ☐ 1 NUMBER OF TEST TRUCKS USED

	PASSES PER TRUCK		
	TRUCK	TYPE	SUSPENSION
TYPE PER FHWA 13 BIN SYSTEM	1	Class 9	Air
SUSPENSION: 1 - AIR; 2 - LEAF SPRING	2		
3 - OTHER (DESCRIBE)	3		

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)
MEAN DIFFERENCE BETWEEN ---

DYNAMIC AND STATIC GVW	1.54%	STANDARD DEVIATION	2.18%
DYNAMIC AND STATIC SINGLE AXLES	-1.38%	STANDARD DEVIATION	2.34%
DYNAMIC AND STATIC DOUBLE AXLES	2.46%	STANDARD DEVIATION	2.37%

8. ☐ 1 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED

9. DEFINE THE SPEED RANGES USED (MPH) ☐ 40 mph _____

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) Sensor #1= .290, Sensor #2= .300

11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) ☒ Yes
IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: Site is set to auto-calibrate every 48 hours. 3 ranges are used. Range #1 is set at 8,000 pounds front axle for trucks weigh up to 32,000 pounds. Range #2 is set for 10,000 pounds front axle for trucks weigh between 32,001 to 50,000 pounds. Range #3 is set for 11,000 pounds front axle for trucks weigh greater than 50,000 pounds.

CLASSIFIER TEST SPECIFICS***

12.*** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:
☐ VIDEO ☐ MANUAL ☐ PARALLEL CLASSIFIERS

13. METHOD TO DETERMINE LENGTH OF COUNT ☐ TIME ☐ NUMBER OF TRUCKS

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:
*** FHWA CLASS 9 _____ FHWA CLASS _____
*** FHWA CLASS 8 _____ FHWA CLASS _____
FHWA CLASS _____
FHWA CLASS _____
*** PERCENT "UNCLASSIFIED" VEHICLES: _____ . _____